


**Feature**

- Small mold type. (DFN1608-2L)
- Low  $I_R$
- High reliability.


**Applications**

- Low current rectification

**Construction**

- Silicon epitaxial planar

**Mechanical Characteristics**

- Lead finish:100% matte Sn(Tin)
- Mounting position: Any
- Qualified max reflow temperature:260°C
- Device meets MSL 1 requirements
- Pure tin plating: 7 ~ 17 um
- Pin flatness : ≤3mil

**Electrical characteristics per line@25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	$V_F$	-	0.53	0.56	V	$I_F=1A$
Forward voltage	$V_F$	-	0.60	0.65	V	$I_F=1.5A$
Reverse current	$I_R$	-	-	50	uA	$V_R=40V$
Junction Capacitance	$C_j$	-	150	-	pF	$V_R=0V, f=1MHz$
Reverse Recovery Time	$t_{rr}$		25		ns	$I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$

**Absolute maximum rating@25°C**

Parameter	Symbol	limits	Unit
Reverse voltage (DC)	$V_{RM}$	40	V
Average rectified forward current	$I_o$	2	A
Typical Thermal Resistance Junction to Ambient	$R_{thja}$	80	°C/W
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load	$I_{FSM}$	12	A
Repetitive Peak Forward Current (Pulse Wave=10ms, Duty Cycle = 25%)	$I_{FRM}$	5	A
Operating and Storage Temperature Range	$T_j, T_{stg}$	-55 to 125	°C

Typical Characteristics




Fig 1. Forward Voltage






Fig 2. Leakage Current

Solder Reflow Recommendation




Remark: Pb free for 260°C; Pb for 245°C.


Product dimension (DFN1608-2L)




TOP VIEW



BOTTOM VIEW



SIDE VIEW




Dim	Millimeters	
	MIN	MAX
A	0.53	0.65
A1	0.13 Ref.	
E	1.55	1.65
D	0.75	0.85
D1	0.60	0.80
D2	0.60	0.80
L	0.025	0.075
H1	0.025	0.075
H2	0.38 Ref.	
H3	0.76 Ref.	
H4	0.36 Ref.	

Notes: This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.


Ordering information

Device	Package	Shipping
PSBD2ED40V2H	DFN1608-2L(Pb-free)	5000 / Tape & Reel

Marking




Load with information



Unit:mm


**IMPORTANT NOTICE**

 and **Prisemi**<sup>®</sup> are registered trademarks of **Prisemi Electronics Co., Ltd (Prisemi)** ,Prisemi reserves the right to make changes without further notice to any products herein. Prisemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Prisemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in Prisemi data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Prisemi does not convey any license under its patent rights nor the rights of others. The products listed in this document are designed to be used with ordinary electronic equipment or devices, Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

Website: <http://www.prisemi.com>

For additional information, please contact your local Sales Representative.

©Copyright 2009, Prisemi Electronics

 **Prisemi**<sup>®</sup> is a registered trademark of Prisemi Electronics.

All rights are reserved.